

DATADOG AGENT

- ▶ Metrics
- ▶ Logs
- ▶ Cluster Agent for Custom HPA

```
datadog:  
  version: "1.21.2"  
  repository: stable  
  values:  
    daemonset:  
      updateStrategy: RollingUpdate  
      tolerations:  
        - key: node-role.kubernetes.io/master  
          effect: NoSchedule  
    rbac.create: "true"  
    kubeStateMetrics.enabled: "true"  
    kube-state-metrics.rbac.create: "true"  
    datadog:  
      apiKey: "${DATADOG_API_KEY}"  
      appKey: "${DATADOG_APP_KEY}"  
      leaderElection: "true"  
      collectEvents: "true"  
    clusterAgent:  
      enabled: true  
      token: "${DATADOG_CLUSTER_AGENT_TOKEN}"  
      metricsProvider:  
        enabled: true
```

DATADOG AGENT (STATSD)

▶ APM/Tracing

```
datadog-statsd:
  chart: datadog
  version: 1.11.2
  repository: stable
  set-values:
    service.annotations.dummyannotation: ""
    daemonset.enabled: "false"
    deployment.enabled: "true"
    kubeStateMetrics.enabled: "false"
  datadog:
    apiKey: "${DATADOG_API_KEY}"
    volumeMounts:
      - name: confd
        mountPath: /etc/datadog-agent/datadog.yaml
        readOnly: true
        subPath: datadog.yaml
    confd:
      datadog\.yaml: |
        use_dogstatsd: true
        dogstatsd_port: 8125
        dogstatsd_non_local_traffic: true
```